

Model	A	B	C	D	E	Max. Load Mount
SW - I & SWB - I	$\frac{3}{8}$ " - 16" M10	$\frac{5}{8}$ " 16 mm	$\frac{7}{8}$ " 22 mm	1 $\frac{1}{4}$ " 32 mm	$\frac{3}{16}$ " 5 mm	6,400 lbs. 2,909 kg
SW-II & SWB-II	$\frac{1}{2}$ " - 13" M12	$\frac{3}{4}$ " 19 mm	1 $\frac{1}{8}$ " 29 mm	1 $\frac{7}{8}$ " 48 mm	$\frac{1}{4}$ " 6 mm	7,000 lbs. 3,182 kg
SW-III & SWB-III	$\frac{5}{8}$ " - 11" M16	$\frac{7}{8}$ " 22 mm	1 $\frac{1}{4}$ " 32 mm	2 $\frac{1}{2}$ " 64 mm	$\frac{5}{16}$ " 8 mm	10,000 lbs. 4,546 kg
SW-IV & SWB-IV	$\frac{3}{4}$ " - 10" M20	1 $\frac{1}{16}$ " 27 mm	1 $\frac{1}{2}$ " 38 mm	3" 76 mm	$\frac{1}{2}$ " 13 mm	13,500 lbs. 5,136 kg

Note: All Fabcel Levelers are plated to provide corrosion resistance; Swivel Levelers swivel 10° each side of centerline. All others approximately 5°. Swivel Levelers can be furnished with patented Fabcel Pads and readily manufactured to customer specifications; also available in stainless steel. For engineering assistance, consult Fabreeka's Engineering Department.

