

Specifications Lev-L Mounts

Type Mount	Base Diam. A	Max. Load	Bolt Size (Diam. x Lg)	Base Height B	Max. Adj. C
210	1 - 5/8" (40 mm)	300 lb (125 kg)	M5 x 30	5/8" (15 mm)	3/16" (5 mm)
220	3 - 1/8" (80 mm)	1,000 lb (450 kg)	M10 x 80	1" (25 mm)	5/16" (8 mm)
230	4 - 3/4" (120 mm)	2,500 lb (1,150 kg)	M12 x 100	1 - 1/4" (32 mm)	1/2" (12 mm)
240	6 - 1/4" (160 mm)	4,500 lb (2,000 kg)	M16 x 120	1 - 3/8" (35 mm)	1/2" (12 mm)
250	7 - 1/4" (185 mm)	10,000 lb (4,500 kg)	M20 x 160	1 - 1/2" (39 mm)	1/2" (12 mm)
260	9" (229 mm)	16,000 lb (7,500 kg)	M24 x 180	2 - 1/8" (54 mm)	1/2" (12 mm)
270	12 - 3/8" (315 mm)	25,000 lb (11,500 kg)	M30 x 200	2 - 3/4" (70 mm)	1/2" (12 mm)

Mount using a thru hole on machine foot allowing adequate clearance and fit. Special length bolts available on request. Consult the factory for details. Custom designs available from the factory.

