

Specifications Lev-L Mounts with Separate Bolt

Type Mount	Base Diam.	Load Range		Bolt Diam. Inches	Minimum Height A	Max. Adjustment B	Overall Height C
		Min/Max lbs	kg				
2 1/2	2 1/2" (57 mm)	125 250	57 114	M8 or 5/16 - 24	1" (25 mm)	2 5/8" (67 mm)	4 1/4" (108 mm)
5	3 1/2" (89 mm)	251 500	114 227	M12 or 1/2 - 20	1 3/8" (35 mm)	4 1/4" (108 mm)	6 5/8" (168 mm)
10	3 1/2" (89 mm)	501 1,000	227 455	M12 or 1/2 - 20	1 3/8" (35 mm)	4 1/4" (108 mm)	6 5/8" (168 mm)
20	7" (178 mm)	1,001 2,000	455 908	M20 or 3/4 - 16	1 7/8" (48 mm)	3 5/8" (92 mm)	6 7/8" (175 mm)
40	7" (178 mm)	2,001 4,000	909 1,818	M20 or 3/4 - 16	1 7/8" (48 mm)	3 5/8" (92 mm)	6 7/8" (175 mm)
80	7" (178 mm)	4,001 8,000	1,818 3,636	M20 or 3/4 - 16	2 1/8" (54 mm)	3 7/8" (98 mm)	7" (178 mm)
120	7" (178 mm)	8,001 12,000	2,727 5,455	M20 or 3/4 - 16	2 1/8" (54 mm)	3 7/8" (98 mm)	7" (178 mm)

Maximum adjustment is reduced by machine foot thickness.

