

| Type | D1 | D2 | H | | L | Max Lifting Capacity ¹ | |
|-------------|-------------------|-------------------|-------------------|-------------------|-------------------|-----------------------------------|-----|
| | | | Deflated | Max. Lift | | lbs | Kg |
| PAL 3-2.5 | 3.20 in 80 mm | 3.20 in 80 mm | 2.50 in 64 mm | 2.75 in 70 mm | 6.20 in 157 mm | 260 | 115 |
| PAL 4-3.5 | 6.00 in 152 mm | 4.00 in 102 mm | 3.50 in 89 mm | 3.75 in 95 mm | 8.00 in 203 mm | 295 | 130 |
| PAL 5.5-2.5 | 3.95 in 100 mm | 3.95 in 100 mm | 2.50 in 64 mm | 2.75 in 70 mm | 6.95 in 177 mm | 480 | 210 |
| PAL 9-4 | 5.10 in 130 mm | 5.10 in 130 mm | 3.65 in 94 mm | 3.95 in 100 mm | 8.15 in 207 mm | 735 | 330 |
| PAL 9-6 | 5.10 in 130 mm | 5.10 in 130 mm | 6.00 in 153 mm | 6.25 in 159 mm | 8.71 in 221 mm | 735 | 330 |

¹At maximum working pressure of 100 psi (7 bar)